

	Type	L #	Hits	Search Text	DBs	Time Stamp	Com m	Er r	Er r
							m	D	r s
							n	e	
							t	i	
							s	o	
								n	
1	B R S	L1	1	6072862.pn.	USPAT	2003/10/12 20:29			0
2	B R S	L2	0	1 and fee	USPAT	2003/10/12 20:29			0
3	B R S	L3	0	1 and charg\$5	USPAT	2003/10/12 20:29			0
4	B R S	L4	0	1 and pay\$8	USPAT	2003/10/12 20:29			0
5	B R S	L5	1	1 and subscri\$6	USPAT	2003/10/12 20:47			0
6	B R S	L6	5	security with destr\$6 with mail	USPAT	2003/10/12 20:50			0
7	B R S	L7	47	destr\$6 with mail	USPAT	2003/10/12 20:50			0
8	B R S	L8	7	7 and (post adj office)	USPAT	2003/10/12 21:11			0
9	B R S	L9	1	7 and recycl\$3	USPAT	2003/10/12 21:11			0
10	B R S	L10	128	recycl\$3 and (post adj office)	USPAT	2003/10/12 21:35			0
11	B R S	L11	75	10 and paper	USPAT	2003/10/12 21:12			0
12	B R S	L12	34	11 and recipient\$1	USPAT	2003/10/12 21:35			0
13	B R S	L13	41	11 not 12	USPAT	2003/10/12 21:22			0
14	B R S	L14	0	recycl\$3 and (post adj office)	EPO	2003/10/12 21:35			0
15	B R S	L15	233	recycl\$3 and (post adj office)	US-PGPUB	2003/10/12 21:36			0
16	B R S	L16	9	(recycl\$3 with recipient\$1) and (post adj office)	US-PGPUB	2003/10/12 21:36			0

6293037

d in Tables I, II, and III, respectively. Tables also contain the corresponding test methods that shall be used to verify conformance with the specified requirements. Test methods that require further information and cannot be easily listed in the table shall be as specified in sections 4.6.2.1 through 4.6.2.3.

Detailed Description Text - DETX (85):

3.3.2 Recycled Materials--In accordance with Federal procurement policy, the USPS encourages the use of the highest percentage of recovered materials practicable in the manufacture and delivery of the finished material specified herein, as long as all specification requirements are fulfilled. The EPA defines recovered material in 40 CFR 250 Section 250.4 paragraph (kk). (See also Federal Register Vol 53, No 23546, Jun. 22, 1988.)

Detailed Description Text - DETX (90):

3.4.1 Adhesion--The non-print side of the face stock shall be coated with a PSA which shall enable the paper to adhere tenaciously for an indefinite period of time to various substrates to which it may be applied. The adhesive shall not